









Parameters	36V-10.4Ah	36V-15.6Ah	36V-20.8Ah	48V-13Ah	48V-15.6Ah
Open Size	1110*500*1230mm	1110*500*1230mm	1110*500*1230mm	1110*500*1230mm	1110*500*1230mm
Fold Size	1110*500*540mm	1110*500*540mm	1110*500*540mm	1110*500*540mm	1110*500*540mm
Net Weight	About 18kg	About 19kg	About 20kg	About 19kg	About 20kg
Frame Material	aluminum-magnesium alloy				
Tire Size	10 inch anti puncture Vacumn tire				
Max Range	45km	70km	100km	75km	100km
Speed	40km/h	40km/h	40km/h	40km/h	40km/h
Rated power	36V/500W	36V/500W	36V/500W	48V/550W	48V/550W
Maximum output power	36V/850W	36V/850W	36V/850W	48V/1100W	48V/1100W
Climbing Angel	25°	25°	25°	30°	30°
Pedal Width	183mm	183mm	183mm	183mm	183mm
Ground Clearance of Pedal	205mm	205mm	205mm	205mm	205mm
Ground clearance of pedal chassis	120mm	120mm	120mm	120mm	120mm
Battery capacity	36V/10.4Ah lithium battery	36V/15.6Ah lithium battery	36V/20.8Ah lithium battery	48V/13Ah lithium battery	48V/15.6Ah lithium battery
Charger parameters	DC42V/2A	DC42V/2A	DC42V/2A	DC54.6V/2A	DC54.6V/2A
Motor driven	Rear wheel drive				
Battery removal method	Portable and removable				
Waterproof level	IP54	IP54	IP54	IP54	IP54
Charging time	5-6 hours				
headlight	LED high-brightness front light 3w				
taillight	Rear LED				
Applicable height	light120 ~ 200cm	light120~200cm	light120 ~ 200cm	light120 ~ 200cm	light120~200cm
Load range	100kg	100kg	100kg	100kg	100kg
Colour	Black、White	Black、White	Black、White	Black、White	Black、White